



## F-Pro Mounted Glass Diameters

Glass thickness 1.8 - 2.2 mm

### F-Pro Mount Thread (SH)

Mount Size	Glass-Ø	outer-Ø
M 30.5 X 0.5	28	32
M 34.0 X 0.5	31	36
M 35.0 X 0.5	32	37
M 35.5 X 0.5	33	37
M 37.0 X 0.5	34	39
M 37.0 X 0.75	34	39
M 37.5 X 0.5	35	39.5
M 38.0 X 0.75	35	39.5
M 39.0 X 0.5	36	40.5
M 40.0 X 0.5	37	42
M 40.5 X 0.5	38	42
M 41.0 X 0.5	38	43
M 43.0 X 0.5	40	45
M 43.0 X 0.75	40	45
M 46.0 X 0.75	43	48
M 48.0 X 0.75	45	50
M 49.0 X 0.75	46	51
M 52.0 X 0.75	49	54
M 55.0 X 0.75	52	57
M 58.0 X 0.75	55	60
M 60.0 X 0.75	57	61.8
M 62.0 X 0.75	59	64.5
M 67.0 X 0.75	64	69.5
M 72.0 X 0.75	69	74.5
M 77.0 X 0.75	74	79.5
M 82.0 X 0.75	79	84.5
M 86.0 X 1.0	83	89
M 95.0 X 1.0	92	97.2
M105.0 X 1.0	102	108
M112.0 X 1.5	107.5	114.5
M122.0 X 1.0	116.5	124.5

### F-Pro Polarizers (DH)

Mount Size	Glass-Ø	outer-Ø
M 27.0 X 0.50	23	29
M 30.5 X 0.50	27	32.5
M 35.5 X 0.50	32	37.5
M 37.0 X 0.75	33	39
M 39.0 X 0.5	36	41
M 40.5 X 0.5	37	43
M 43.0 X 0.75	39	46
M 46.0 X 0.75	42	49
M 48.0 X 0.75	44	50
M 49.0 X 0.75	45	51
M 52.0 X 0.75	48	54
M 55.0 X 0.75	51	57
M 58.0 X 0.75	54	59.6
M 60.0 X 0.75	56	61.5
M 62.0 X 0.75	58	64
M 67.0 X 0.75	63	69
M 72.0 X 0.75	68	74
M 77.0 X 0.75	73	79
M 82.0 X 0.75	78	84
M 86.0 X 1.0	82	89
M 95.0 X 1.0	91	97
M105.0 X 1.0	101	108.5
M112.0 X 1.5	106	115.5
M122.0 X 1.0	118	125.5



**B+W**  
FILTER